

HEALTH HAZARDS (ACUTE AND CHRONIC):

Acute: Eyes: Moderate irritant Skin: Moderate irritant Inhalation: High concentrations of vapors may produce irritation of the respiratory tract, headache, dizziness, and nausea. Ingestion: Similar to inhalation.
Chronic: Prolonged repeated overexposure to this product may lead to skin sensitization or dermatitis.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No
ACGIH CARCINOGENICITY: No

TOXICITY DATA:

INGREDIENTS ORAL LD50 (RAT) DERMAL LD50 (RABBIT) INHALATION LC50 (RAT)
N/A

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush well with water. Contact a physician if irritation persists.
SKIN: Wash with soap and water.
INHALATION: Remove patient to fresh air. Contact a physician.
INGESTION: Do not induce vomiting. Contact a physician. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Prevent skin and eye contact. Use non-combustible material to confine and/or absorb. Eliminate ignition sources. Ventilate area.

WASTE DISPOSAL METHOD: Remove to a waste disposal facility operating in compliance with federal, state, and local regulations.

Proper Shipping Name: Non-Hazardous according to IATA, 49CFR and IMDG regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: If mists are generated in the use of this product; then the following values for petroleum oils apply.

---ACHIG - TLV/TWA = 5 mg/m³/8hr

---OSHA - PEL/TWA = 5 mg/m³/8hr

---ACGIH - TLV/STEL = 10 mg/m³

---'Empty' containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, sparks, flames, static electricity, or other sources of ignition.--- Use with adequate ventilation.

OTHER PRECAUTIONS: WARNING: Many hot organic chemical vapors or mists are susceptible to sudden spontaneous combustion when mixed with air. Ignition may occur at temperatures below those published in the literature as "autoignition" or "ignition" temperatures. Ignition temperatures decrease with increasing vapor volume and vapor/air contact time, and are influenced by pressure changes.

Ignition of organic chemical vapors may occur at typical elevated-temperature process conditions, especially in processes operating under vacuum if subjected to sudden ingress of air, or outside process equipment operating under elevated pressure if sudden escape of vapors or mists to the atmosphere occurs.

Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established

and maintained.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION: None required for normal use with adequate ventilation.

In poorly ventilated areas, use NIOSH approved organic vapor respirator.

VENTILATION: Local exhaust is recommended for confined areas. General

mechanical ventilation is adequate for normal use.

PROTECTIVE GLOVES: Chemical resistant rubber gloves, such as Polyvinyl chloride-coated, and other protective gear as required to minimize skin contact.

EYE PROTECTION: Safety glasses. Splash proof goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye bath and safety shower.

WORK/HYGIENIC PRACTICES: Follow current H.M.I S. regulations.

===== SECTION IX - DISCLAIMER =====

ITW DYKEM bases the information and recommendations in this document on data believed to be correct. No warranty of any kind, however, is made as to the information in this document.